

WE CLAIM:

1. An apparatus for cleaning a golf club, comprising:
a base having an aperture; and
an open slot extending from the aperture to an edge of the base.
2. The apparatus of claim 1, further comprising a closed slot in the base.
3. The apparatus of claim 1, further comprising an alignment channel in the base.
4. The apparatus of claim 1, further comprising a divot tool.
5. The apparatus of claim 4, wherein the divot tool comprises:
a U-shaped end at one end of the divot tool;
a recess at another end of the divot tool; and
a stud between the U-shaped end and the recess.
6. The apparatus of claim 5, further comprising a ball marker that includes a stem.
7. The apparatus of claim 6, wherein the stem passes through the stud.
8. The apparatus of claim 1, wherein one edge of the base is tapered.

9. An apparatus for cleaning a golf club, comprising:
a golf shoe;
a base attached to the golf shoe; and
an open slot extending to an edge of the base.
10. The apparatus of claim 9, wherein the base comprises a closed slot.
11. The apparatus of claim 9, wherein the base comprises an alignment channel.
12. The apparatus of claim 9, wherein the base is permanently attached to the golf shoe.
13. The apparatus of claim 12, wherein the base is permanently attached to an upper of the golf shoe.
14. The apparatus of claim 9, wherein the base is removeably attached to the golf shoe.
15. The apparatus of claim 14, wherein the base is removeably attached to an upper of the golf shoe.
16. An apparatus for cleaning a golf club, comprising:
a golf shoe;
a base attached to an upper of the golf shoe;
the base includes:
an aperture;
an open slot extending from the aperture to an edge of the
base; and

an alignment channel.

17. The apparatus of claim 16, further comprising a closed slot in the base.

18. The apparatus of claim 17, further comprising a divot tool.

19. The apparatus of claim 18, wherein the divot tool includes a stud for insertion into the closed slot in the base.

20. The apparatus of claim 19, further comprising a ball marker.

21. The apparatus of claim 16, wherein one edge of the base is tapered.

22. A golf shoe, comprising:
an upper;
a base attached to the upper;
the base includes:
5 an aperture;
an open slot extending from the aperture to an edge of the
base;
a closed slot;
an alignment channel;
10 a divot tool removeably attached to the base; and
a ball marker removeably attached to the base.

23. The apparatus of claim 22, further comprising a shoelace that passes through the open slot and into the aperture.

24. The apparatus of claim 22, wherein the divot tool includes a stud.

25. The apparatus of claim 24, wherein the ball marker includes a stem that passes through the stud.

26. The apparatus of claim 22, wherein one edge of the base is tapered.

27. A method for cleaning a golf club, comprising:
moving a blade of a golf club relative to a blade scraper; and
removing debris from the blade of the golf club;
wherein the blade scraper comprises:

5 a base having:
 an aperture;
 an open slot extending from the aperture to an edge
of the base;
 a closed slot; and
10 an alignment channel.

28. The method of claim 27, wherein the base is permanently attached to an upper of the golf shoe.

29. The method of claim 27, wherein the base is removeably attached to an upper of the golf shoe.

30. The method of claim 29, wherein a shoelace passes through the open slot and into the aperture.

31. The method of claim 27, wherein the step of moving comprises the blade being in a fixed position.

32. The method of claim 27, wherein the step of moving comprises the scraper being in a fixed position.